

## GlideinWMS - Feature #11155

### Collect job runtime history in htcondor attributes

12/15/2015 04:51 PM - Marco Mambelli

<b>Status:</b>	New	<b>Start date:</b>	12/15/2015
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>		<b>% Done:</b>	0%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>		<b>Spent time:</b>	0.00 hour
<b>Stakeholders:</b>			
<b>Description</b>			
<p>Many jobs start running on one glidein and then are preempted, evicted or otherwise interrupted and continue on a different glidein, maybe on a different site. The list of sites where the job ran and possibly also the times at each site should be collected to improve the understanding of the job and the sites and to allow for a more correct accounting.</p> <p>HTCondor is tracking where the job is running via: CurrentHosts - is the # of hosts AllRemoteHosts - are all the nodes used by a MPI job (during the last execution) RemoteHost <del>not documented</del> is the current host (when running) LastRemoteHost <del>not documented</del> is the last host where the job ran</p> <p>SYSTEM_JOB_MACHINE_ATTRS = \$(SYSTEM_JOB_MACHINE_ATTRS),RemoteHost SYSTEM_JOB_MACHINE_ATTRS_HISTORY_LENGTH = 10</p> <p>HTCondor will save: MachineAttrRemoteHost0 MachineAttrRemoteHost1 ... MachineAttrRemoteHost9</p> <p>A question is if this is of interest enough for GlideinWMS or if it should be delegated to accounting (e.g. Gratia)</p>			

### History

#### #1 - 01/04/2016 02:19 PM - Parag Mhashilkar

I think this is a great feature to request from HTCondor guys. In the end, job jobs from one startd to the other, glidein or no glidein does not change this fact.