

art - Milestone #1144

Defining categories for the error logger

04/04/2011 11:45 AM - Rob Kutschke

Status:	Accepted	Start date:	04/04/2011
Priority:	Normal	Due date:	09/30/2013
Assignee:		% Done:	0%
Category:	Infrastructure	Estimated time:	16.00 hours
Target version:		Spent time:	0.00 hour
Experiment:	-		
Description			

History

#1 - 04/04/2011 11:51 AM - Rob Kutschke

At the last Friday meeting I showed some of my proposed example code for an art example package. The first module uses `std::cerr` to print the event number. Chris suggested changing it to use `LogInfo`. My first thought was that this makes sense. But it does not really make sense to introduce the message logger system without describing what categories mean and how to use them. I am a little worried that this is getting too overwhelming for one of the intended audiences. Any suggestions here? Maybe a category of "Heartbeat"? All of the examples that I have generate only heartbeat messages. Does the current message logger have an interface that takes a category type so that we can restrict the categories used by people?

#2 - 12/09/2011 03:31 PM - Walter E Brown

- *Tracker changed from Feature to Meeting*

#3 - 07/25/2013 01:57 PM - Christopher Green

- *Tracker changed from Meeting to Milestone*

- *Due date set to 09/30/2013*

- *Category set to Infrastructure*

- *Status changed from New to Accepted*

- *Estimated time set to 16.00 h*

- *Experiment - added*

#4 - 04/17/2015 10:20 AM - Kyle Knoepfel

- *Target version set to 521*

#5 - 10/23/2017 12:12 PM - Kyle Knoepfel

- *Target version deleted (521)*