GlideinWMS - Feature #4904

Specify a default for GWMS_XSLT_PLUGIN_DIR

11/04/2013 04:19 PM - Burt Holzman

Status:	Assigned		**Start date:**	11/04/2013
Priority:	Normal		**Due date:**	
Assignee:	Marco Mambelli		**% Done:**	0%
Category:	Factory		**Estimated time:**	0.00 hour
Target version:	v3_7_x		**Spent time:**	0.00 hour
Stakeholders:	OSG			

Description

Rather than deal with [#4846](#4846), Tony pointed out we could just adopt the following logic.

If GWMS_XSLT_PLUGIN_DIR or the option is not specified, look for a specific path (plugins.d?) on the same directory level as the configuration file as the default.

That should make life easier for machines with multiple factories, frontends, etc.

Related issues:

Related to GlideinWMS - Feature #4846: Include GWMS_XSLT_PLUGIN_DIR setting i...	**Assigned**	**10/25/2013**

History

#1 - 11/21/2013 08:46 AM - Burt Holzman

- Target version changed from v3_2_3 to v3_2_x

#2 - 04/01/2015 01:41 PM - Parag Mhashilkar

- Related to Feature #4846: Include GWMS_XSLT_PLUGIN_DIR setting in generated {factory,frontend}_startup added

#3 - 04/01/2015 01:43 PM - Parag Mhashilkar

- Assignee changed from Burt Holzman to Marco Mambelli

- Target version changed from v3_2_x to v3_2_10

- Stakeholders updated

#4 - 05/14/2015 02:21 PM - Parag Mhashilkar

- Target version changed from v3_2_10 to v3_2_x

#5 - 04/26/2018 04:44 PM - Marco Mambelli

- Target version changed from v3_2_x to v3_4_x

#6 - 09/06/2018 03:25 PM - Marco Mambelli

- Target version changed from v3_4_x to v3_5_x

#7 - 10/04/2019 04:56 PM - Marco Mambelli

- Target version changed from v3_5_x to v3_6_x

#8 - 02/14/2021 08:04 PM - Marco Mambelli

- Target version changed from v3_6_x to v3_7_x